AUBURN-CORD-DUESENBERG CLUB
CORD L-29 FRONT DRIVE JUDGING STANDARDS

	Auth	Cond

EXTERIOR 120/180

METALWORK	30		45	
Proper Sheetmetal & Panel Fit(steel w/hidden wood structure) - Notify CJ if rebodied/non-orig components	2		10	
Hood top/sides, riveted lift handles(BC); screwed hooks (latches) & hood brackets(CHR), leather/rubber pad (LTH/RUB); corner guards(LTH) w/bottom stitch & rivet(NI); center hinge, end caps(CHR)	4		4	
Radiator shell (BC/CHR); shutters (BC); differential cover(BC), trim(CHR) & lower front bolts(CHR); headlamp bracket(BC) & tie rod(BLK); riveted bracket to brake housing(BC) w/acorn nut & washer(CHR)	6		3	
Brake housings(BC), early solid(BC), mid-drilled w/dealer louvres(ALM), then factory louvres(BC), shoe anchor pin nuts(BC)	2		4	
Front fenders, stamped trim mouldings, underside, braces, fasteners; side mount locking posts(BC/TC); battery box cover(Early BLK, later BC/TC/CC)	3		4	
Core body - cowl; cowl vents; side vents; windshield frame & visor(closed cars); raised mouldings(BC/TC)	2		4	
Doors & door hinges(Closed BC/TC, Open CHR); Cab golf door & rumble seat lid(BC/TC) w/BC hidden hinges;	2		4	
Running boards(BC top/CC under), fasteners(CC) Front rubber pad assy, treads(RUB), trim, end caps, screws(CHR)	2		3	
Rear fenders & stamped raised mouldings(BC/TC); underside, fasteners(BC/TC); rear body panel; gas tank cover(BC/TC);	3		4	
Pads for headlamp bracket, door handles & rear light standards(BLK paper, hidden) ; Molded radiator shell grommets; horn & side mount grommets(RUB)	2		3	
Weltings 1/4" on fenders; running boards; rear body(BLK); terminated and tucked under.	2		2	

PAINT	20		50	
Exterior paint in L-29 colors & style, including trim & pinstripes if present, across all body panels, mouldings, fenders, headlamp brackets, closed car windshield frame, visors(BC/TC)	10		20	
Front Bumper mounting bar, support bracket, castellated nut in front(CC); clamps, arcs & license plate bracket(CC); safety fold tab plates or safety wired bolts(CC)	5		5	
Rear Bumper outer mounting brackets; inner support arms & castellated end nuts, riveted license plate bracket w/bolted plate; rear step(Cab) (BC/CC) w/tread(RUB)	5		5	
Uniformity (appears to be lacquer) & Uniform shine			20	

PLATING	30		25	
TWILITE Headlamps(CHR); side cowl lamps(CHR); cowl lamp brackets early(straight), late(pointed) ends(CHR)	6		4	
Radiator cap(CHR w/half-moons(BC); Differential cover trim & bolts, Cord emblem(2-piece on CHR cap)	3		3	
Front Bumper impact rails(CHR/unpolished back); ornamental clamps & bolts(CHR w/red/black/plain grooves); Hightop clamp acorns & end bolt heads, castellated end nuts(CHR)	3		3	
Windshield Frame(Cabriolet & Phaeton)(CHR)	3		2	
Cowl molding(CHR); Side mount h/w(CHR); battery box wingnuts(CHR); Running board lamps(4-D cars)(CHR)	2		3	
Door handles, screws(NI); latches, guides, striker plates & screws(CHR), striker(anond NI); Pht/Cab hinges(CHR); Cab Rear deck latch, round bumper plate(CHR)	6		4	
Rear Bumper impact rails(CHR/unpolished back); ornamental clamps (CHR w/red/black/no grooves)	3		3	
Tail lamp; stop/back up lamp on standards w/acorn nuts (CHR)	4		3	

AUBURN-CORD-DUESENBERG CLUB
CORD L-29 FRONT DRIVE JUDGING STANDARDS

	Auth		Cond	
CONVERTIBLE TOP BOOTS AND CURTAINS	**20**		**35**	
Proper Haartz Cloth(Mossy Green or BLK), rear deck snaps, side snaps Cab-5, Pht-9 (hidden)	10		15	
Canvas/leather bindings w/tips(NI), Vertical top binding (CHR plated zinc)	3		5	
Visor(BC/TC) w/polished aluminum trim; wiper arms(CHR)	2		5	
Rear curtain(Haartz Cloth), window frame(CHR), Lift-the-Dot fasteners(7 or 9 across), Haartz cloth boot cover(HC/BLK)	3		5	
Weatherstripping condition	2		5	
OR				
SEDAN ROOF	**20**		**35**	
Proper Haartz Cloth(Mossy Green), seams, padding, fit	10		15	
Drip channels(AL) w/fabric bead over doors; L-corners and finishing nails(NI); end finish(BR early/AL late); nailer trim(AL) w/fabric bead above visor; Strip at bottom of windshield(CHR)	5		10	
Bottom of windshield visor(BC/BLK), hidden wiper arms, windshield channels, top/bottom weatherstripping, retaining strip (CHR)	2		3	
Door window channel felts, weatherstripping	3		7	
TRUNK RACK, WHEELS/TIRES, TOOLS, SIDE MOUNTS	**15**		**15**	
Trunk rack(BC/CC) including all fasteners(CC)	4		4	
Spoked wheels (BC/TC or CHR) & retaining ring(CHR)	3		2	
Correct hubcaps & dummy side mounts (CHR, Red/Black half-moons, Red/Blk/Plain grooves)	2		3	
6 Tires(BW/Dbl WW); 90° stems w/Schrader tool caps(NI). No deduct for period plain caps	3		4	
Side mount covers w/silk-screened CORD emblem, straps(2 LTH, 3rd for mirrors)	1		1	
Jack & handle(paint olive drab; 2 versions); tool kit	2		1	
GLASS	**5**		**10**	
Clear glass on windshield; doors; quarter(sedan); rear window (closed); curtain correct glass size (cab/pht)	1		4	
TWILITE HEADLAMP lenses, marked	2		3	
TWILITE lenses Side/Cowl(frosted); Tail Left(red); Right(Early Clear, later Red/Clear)	2		3	

INTERIOR 170/130

	Yes		No	
FIRE EXTINGUISHER				
UPHOLSTERY	**40**		**30**	
Leather(open cars) or English broadcloth(closed cars)	10		10	
Seat cushion patterns; pleats; buttons; bindings; trim	10		5	
Door panels & pleats(later cars); proper(or no) broadlace trim(closed cars)	5		5	
Under-dash, left side pocket, right side pocket (open); right tools swing panel (closed); rear deck cubbys (cab)	5		5	
Back of front seat; rear armrests; dropdown center armrest(Brougham only); Rumble seat(Cab)	10		5	

AUBURN-CORD-DUESENBERG CLUB
CORD L-29 FRONT DRIVE JUDGING STANDARDS

	Auth		Cond	
FLOORS AND COVERINGS	**20**		**15**	
Serial/Engine (Right front), Body (Right or Left) tags under carpet, Miller patent tag optional	2		2	
Wilton carpet, installed properly w/sewn bindings	10		7	
Proper Firewall penetrations; Engine cover; carpeted on bottom; black on top	4		2	
Patterned steering column & pedal plate; heel pad; brake lever; muffler bypass control floor plates(RUB)	2		2	
Tool Pan; hinges & lock under rear carpet; or under rumble seat floor on cabriolet	2		2	

HEADLINER BOWS AND PADS	**20**		**15**	
Top slats, hinges, windshield & removable pillar (phaeton) H/W, thumbscrews, hold-down brackets, deck lid remote handle(Cab, NI); rubber base on rear bow	10		10	
Top deck(front) (Bodril); top, rear, & rear bent bows(Bodril covered or NAT); rear bow finish plates, rear bent bow support irons (CHR)	5		3	
Stay straps connected to loops on rear bent bow and rear deck (Pht only); Curtain holdback dot fasteners on bow	5		2	
OR				
SEDAN HEADLINER	**20**		**15**	
Broadcloth headliner material w/proper trim	10		5	
Windshield regulator board, w/round bolts & washers	5		5	
Rear window roller, curtain & tasseled pull cord	5		5	

INSTRUMENT PANEL	**30**		**25**	
Instrument board painted w/crinkle finish; control bezel w/smooth finish; plated screws & washers(NI)	5		5	
German silver backing plates w/crinkle finish	5		5	
German silver glove compartment w/lock & Cord emblem	2		3	
Map light & cigar lighter(not present early cars, added by Engr bulletin), correctly located above glove box.	2		1	
Ignition switch & CORD keys	2		1	
Correct Instruments & lights, dial faces, glass, lighting	4		3	
Controls, two panels of four for closed, two panels of three for open cars, correctly located w/labels	6		5	
Open cars: Wiper motors & escutcheons on instrument panel,w/question mark vac tubes(no rubber). Closed: Motors behind windshield regulator board	4		2	

CONTROLS, WHEEL, PEDALS AND LEVERS	**20**		**15**	
Ridged steering wheel w/ridges & finger grip (BLK), steering column tube, clamp, & collar(CHR/NI)	5		3	
Headlight ring w/white line & horn button, headlight dimmer switch(late models)	3		3	
Shifter rod(CHR) w/ridged Bakelite or optional Onyx knob, under dash retainer on firewall, horizontal rollers behind instrument panel	3		3	
Brake & Clutch pedals(BLK) w/rubber pads, accelerator & Bijur pedals(BLK)	4		3	
Emerg brake; muffler bypass levers(NI), top vent(NI); side cowl vent levers(BC); front seat adjuster(closed)	5		3	

AUBURN-CORD-DUESENBERG CLUB
CORD L-29 FRONT DRIVE JUDGING STANDARDS

	Auth		Cond	
ELECTRICAL SYSTEM	**20**		**15**	
Dome, & reading lamps(NI), manual switches, auto door light switch(closed cars), step lamps(4D cars), rear compartment lamp (rumbleseat on Cab) (NI)	5		3	
Integrated coil(BLK) & ignition switch(NI) under dash; Current limit relay under dash, top of engine cover	5		2	
Correct wiring harnesses, wrappings, stays(AL), routed correctly through firewall, frame, pillars	10		10	
HARDWARE	**20**		**15**	
Interior door handles & locks, window cranks for doors, windows; rear view mirror(NI)	8		6	
Door & window garnish mouldings Closed(walnut), Open(CHR), Glass surround(CHR, open cars)	5		3	
Rear armrest cigar lighter (closed cars, right side only) & ash receivers (closed, both sides)	2		1	
Scuff plates(AL) w/Black CORD logo	2		2	
Robe rail(NI), foot rest(NI & carpet, 4D cars), toggle grips (closed cars)	3		3	

ENGINE AND CHASSIS 165/135

ENGINE AND FUEL SYSTEM	**35**		**30**	
Correct Engine FDA(thru 4444;appx 3/'31); FF afterwards	5			
Engine tag(below generator); engine # crankcase stamp (left or right)	1		1	
CORD green (John Deere Green) Block; head; crankcase, oil pan, timing chain, trans covers(EC); differential & lower flywheel covers(BLK)	3		5	
Acorn nuts on head(27) & timing chain case cover(3, NI/CHR); cable stand-offs (1-left, 2-right, NI/CHR)	3		2	
Oil filler tube(EC); cap(CHR or NI); Dipstick w/polished handle or separate in early cars, laid on head	2		2	
Cylinder side plate (NI/CHR); slotted round head screws, copper washers	2		3	
Engine temp sensor(NAT/BR); line(NI); separate firewall entry grommet	1		1	
Accelerator linkage(NI rods w/BLK front); & return spring (BLK), spring clip(NI/CHR)	1		2	
Schebler Duplex Model "S" dual updraft carb (NAT/BLK) w/ acorn nut; linkage; correctly routed and connected choke & throttle wires w/band(NI)	4		2	
Correct Fuel Pump tall(up to 2928239); short(later)(NAT)	3		2	
Intake manifold (BLK porc) Early/late (w/riser after 3932); vacuum fitting & line (NI) to firewall grommet	3		3	
Valve tappet covers & hex bolts(NI); ventilator tube (straight, plated/late(flex to carb, after 2928388) (BLK/CHR)	2		2	
Oil filter can w/label; clamp bracket; fasteners(BLK)	2		2	
Oil pressure regulator(EC); cap(NAT/AL); line(Copper)	1		1	
Plumbing; fuel; oil; vacuum lines(Copper) routed correctly	2		2	
ENGINE COMPARTMENT	**30**		**25**	
Firewall/Under hood(BC); hinge trough(BLK/BC); cowl vent tubes(BC). Miller patent tag(right FW, mid-1930+)	2		3	
C-Radiator Supports(BLK, open side in); hood support hooks(BLK) w/tubes(leather/rubber); riveted cowl lacing (small rivets on radiator, large on cowl), speedometer cable w/ separate firewall grommet	3		3	
Correct firewall layout; lines; tubes; cables; grommets	5		2	
Firewall L/R toeboards; top insulator(Gray/WHT)	2		2	

AUBURN-CORD-DUESENBERG CLUB
CORD L-29 FRONT DRIVE JUDGING STANDARDS

	Auth	Cond
Bijur tank & pump(BLK); cap label; lines & fittings(NI), Type A, B, C	3	2
Brake supply tank, bracket(BLK); decal; copper brake lines w/woven tar loom where needed	2	2
Gemmer steering box(BC); plated tube; steering column; clamp(NI)	3	3
Brake & Clutch pedals; linkage; springs; fasteners(BLK)	2	2
Splash Pans(BLK); no left pan on early cars; louvres & raised drip tray below fuel pump added(3 types)	3	3
Transmission case 2/4-bolt after 2926500; breather tube(EC); lubricant filling plug(EC, early-side of case, later-2 types on top); Advisory (Whitmore/Enterprise)	2	3
Lower & upper shift rods; ball-joint & fitting; roller bracket(EC); rollers, cotter pin (2/early cars); adjusting nut on back of top roller; Front & rear shift rods(NI/CHR); firewall entry (no grommet)	5	3
CHASSIS	**30**	**25**
Front Axle; Springs; cast cups; shackle cases/safety wire; drive shafts; U-joints(CC); dust covers (NAT); 45° Alemite fittings	10	8
Steering Linkage: Ball arm, nut, drag link, tie rod, and tie rod ends(CC)	4	4
Brake drums(3/5 ribs); housings(CC); master cylinder (BLK), stop light wire, copper brake lines, front & rear "T" connections on frame, brackets, Brake lines & hoses	4	3
Houdaille Shocks(CC)	2	2
Handbrake components on rear engine cover(EC); rods, rear cross-shaft, linkages on rear plate (CC)	2	2
Rear axle & plates; springs; shackles; fasteners; cylindrical rebound rubbers (CC); Bijur fittings on front & rear of spring connections	4	3
Gas tank; tank guard; straps; fasteners (CC), gas gauge tank unit & wiring	4	3
ELECTRICAL SYSTEM	**30**	**25**
Correct C7(brass hat) spark plugs; C10 listed in parts book, but incorrect	2	2
Spark plug, coil wires oak/red w/black stripes; routed through manifolds; Coil & condenser wires, spark advance cable thru no-grommet firewall hole	3	2
Lead manifolds; supports(NI/CHR); spark cable, w/standoff (NI/CHR)	2	2
Distributor(BLK); cap(brown); tag; adv plate; grease cup (NI); condenser(NAT)	3	2
Generator(BLK) Early(short w/rectangular tag), or long w/oval tag (changed @2927017); relay cover(CHR or BLK); drive coupling (BLK/RED); cable & wiring	3	3
Oil level gauge(NAT) & wiring (BLK tar woven), Rear(frame) terminal block; wiring	3	3
Steering column headlight switch; shroud terminal block; cloth wrapped cable assemblies	3	3
Horns; wiring; rivet bracket(BLK); grommets; acorns (CHR)	3	3
Backup switch(NAT/BLK); bracket/cover & hex bolts(EC)	3	1
Starter & mtg bolts(BLK); brush cover(NI); cap; oilers, solenoid, spring; ctrl cable; wiring/loom(BLK)	2	2
Battery mountings; clamps; NEG terminal cable(BLK) to starter, POS terminal(braided) to frame	3	2
COOLING SYSTEM	**20**	**15**
Fan 4/6 blades(unpolished); bearing; mount(EC); oiler	2	2
Fan belts(1 or 2; Red or BLK)	2	2
Fan shroud(BLK); riveted antisqueak lacing	3	2
Modine radiator; Pine Winterfront thermostat w/tag; drain cock(BLK)	2	2

	Auth	Cond
Thermostat housing & bolts(EC)	2	2
Radiator Hoses Upper/Lower radiator; water pump; side plate(Red/BLK); extension tubes(NI)	3	1
Hose Clamps; flat dual strap style(NI/CHR)	3	2
Water pump(EC); Bijur fitting or grease cap(NI); packing nuts(BR), coupling hose(Red/BLK); pressure clamps(NI/CHR)	3	2

EXHAUST SYSTEM	**20**		**15**	
Exhaust manifold(BLK Porcelain) w/2 screws for air cleaner (Early/late)	7		4	
Manifold heater valve(BC); outlet tube(NI, changed to larger tube after FD3932); control cables(CAD) & standoffs(NI/CHR)	4		3	
C-pipe(BLK); insulating sock (WHT) to X-member; 4 clamps(NI)	2		2	
Muffler(BLK); bypass assembly & control cable; outlet pipe & clamps (Early/late after 26903)	4		3	
Tailpipe early(round, BLK) / late (flat, NI) & fasteners	3		3	

FACTORY ACCESSORIES

FACTORY ACCESSORIES(max 3 points)	**Max 3**			
BONUS POINTS - 1 point each - maximum of 3				

As published in the Auburn Authorized Accessory Guide	
Pilot Ray Automatic Driving Light	1
Pilot Ray Duplex Lights	1
Lorraine Driving Lights	1
Phinney Walker Clock(Glove Box), opt monogrammed	1
Combination PW Clock & Rear-view Mirror	1
Metal Tire Covers	1
Cord (Potter) Trunk w/optional two suitcases	1
Safety Driving Lights(front fenders)	1
Radiator Grille Chromed	1
Fry Seat Covers(Closed Cars only)	1
Disappearing Rumble or Rear Seat Windshield	1